

STARTZILLA 12024 XT



XT
RANGE

12V

24V



LED LIGHT



TEST



SUPPLY



START

NEW

- Multi-functional electronic starter, power supply unit and tester con LiFePo4 lithium battery for 12/24V cranking (12000A start max). With LCD display.
- OVER RIDE function for cranking in emergency conditions with no battery or completely flat.
- SUPPLY function for stable power supply during battery changes.
- Battery TEST function (cranking efficiency/charge status) and alternator.
- High efficiency led for use as emergency light.

DESCRIPTION

Multifunction electronic starter, power supply and tester, with LiFePO4 lithium battery for 12V/24V starting of cars, vans, small boats, lorries etc.

It performs control tests on the battery: voltage at terminals, starting capacity (CCA) and operational check of the vehicle alternator.

The OVER RIDE function allows starting in emergency conditions when battery is missing (or completely down).

It is a stable and reliable power supply source for battery charges (SUPPLY function).









Robust and compact, it is equipped with high intensity LED light.

Protection against: polarity reversal, short-circuit, overvoltage (incompatible battery voltage), undervoltage (cut-off voltage), overcurrent, overheating, under-temperature, accidental contacts, alternator return currents.

Complete with starting cables and wall charge.



TECHNICAL DATA

| | | |
|--|--|--|
|  CODE CODE 829528 |  CHARGE MAINS VOLTAGE 1ph 100 - 240 V |  STARTING VOLTAGE 12 / 24 V |
|  MAX STARTING CURRENT 12000 / 6000 A |  225 / 200 Ah |  PROTECTION DEGREE IP43 |
|  DIMENSIONS (LxWxH) 15,5 x 23,4 x 31,8 cm |  WEIGHT 4,580 kg | |

DOWNLOAD

- 
 CATALOG IMAGE
- 
 INSTRUCTION MANUAL
- 
 SPARE PARTS LIST
- 
 BROCHURE